



US009636878B2

(12) **United States Patent**
Mast et al.

(10) **Patent No.:** **US 9,636,878 B2**
(45) **Date of Patent:** **May 2, 2017**

(54) **MOLDING APPARATUS AND METHOD FOR APPLYING POSITIVE PRESSURE TO MOLDED CONTAINER**

(71) Applicant: **Amcors Limited**, Hawthorn, Victoria (AU)

(72) Inventors: **Luke A. Mast**, Brooklyn, MI (US);
Peter Bates, Chelsea, MI (US);
Bradley Wilson, Manchester, MI (US)

(73) Assignee: **Amcors Limited**, Hawthorn (AU)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 312 days.

(21) Appl. No.: **14/364,079**

(22) PCT Filed: **Jan. 4, 2013**

(86) PCT No.: **PCT/US2013/020260**

§ 371 (c)(1),

(2) Date: **Jun. 10, 2014**

(87) PCT Pub. No.: **WO2013/103798**

PCT Pub. Date: **Jul. 11, 2013**

(65) **Prior Publication Data**

US 2014/0306384 A1 Oct. 16, 2014

Related U.S. Application Data

(60) Provisional application No. 61/583,336, filed on Jan. 5, 2012.

(51) **Int. Cl.**

B29D 22/00 (2006.01)

B29C 49/00 (2006.01)

(Continued)

(52) **U.S. Cl.**

CPC **B29D 22/003** (2013.01); **B29C 49/00** (2013.01); **B29C 49/185** (2013.01); **B29C 49/42** (2013.01); **B29C 49/44** (2013.01)

(58) **Field of Classification Search**

None

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,352,402 A 10/1994 Orimoto et al.

5,445,515 A 8/1995 Orimoto et al.

(Continued)

FOREIGN PATENT DOCUMENTS

JP 2003-103609 A 4/2003

KR 100119008 B1 9/1997

(Continued)

OTHER PUBLICATIONS

International Search Report and Written Opinion for PCT/US2013/020260, mailed Jun. 27, 2013; ISA/KR.

Primary Examiner — Monica Huson

(74) *Attorney, Agent, or Firm* — Harness, Dickey & Pierce, PLC

(57)

ABSTRACT

A method of forming a container includes blow molding a primary form of the container inside a primary mold. The primary form has an exterior surface. The method also includes applying a fluid to the exterior surface of the primary form to shrink the primary form and to form a shrunken form of the container. Furthermore, the method includes blow molding a secondary form of the container from the shrunken form inside a secondary mold.

16 Claims, 2 Drawing Sheets

